




Marvo

Recess Zoom Light-Movable



Application Areas



OFFICES



BANKS



HEALTHCARE



RETAIL



EDUCATIONAL
INSTITUTE



COMMON
AREA



Marvo

RECESS ZOOM LIGHT - MOVABLE

The design features a fully enclosed, precision die-cast aluminium construction with smooth pan and tilt adjustment for flexible aiming. This adjustable recessed single-chip COB downlight is equipped with a high-quality aluminium reflector to ensure efficient, consistent illumination.

Luminaire Details


Product Name	: Marvo
Product Type	: COB Zoom Light
LED Type	: COB
Fixture Type	: Recess Mount
Dimmable	: 0-10V, DALI, Phase-Cut

Luminaire Source Details

Light Emission	: Indoor Focus Lighting
Source Brand	: Bridgelux / CITIZEN
CRI	: ≥80
McAdam Binning	: Step 5

Luminaire Housing

Body	: Die-Cast Aluminium
Reflector	: Yes
Diffuser Type	: Clear
Operating Temperature	: -10° to 50° C
Humidity	: RH 10-90 %
IP Rating	: IP20



Ingress Protection
IP20

LM
79

LM
80

TM
21

Technical Specifications

Wattage	12W	20W	30W	40W
Product Code	MRV-RZL-12	MRV-RZL-20	MRV-RZL-30	MRV-RZL-40
Nominal Input Voltage	240V AC, 50Hz	240V AC, 50Hz	240V AC, 50Hz	240V AC, 50Hz
Luminous Flux	1200*	2000*	3000*	4000*
Color Temperature	6500K/4000K/3000K	6500K/4000K/3000K	6500K/4000K/3000K	6500K/ 3000K
CRI	≥80	≥80	≥80	≥80
P.F.	>0.95	>0.95	>0.95	>0.95
THD	<10%	<10%	<10%	<10%
Surge Protection	Up to 4KV	Up to 4KV	Up to 4KV	Up to 4KV
IP Rating	IP20	IP20	IP20	IP20
Beam Angle	24°/36°/60°	24°/36°/60°	24°/36°/60°	24°/36°/60°
Mounting	Recess	Recess	Recess	Recess
Fixture Color	White	White	White	White
Cutout(mm)(∅)	74	83	105	125
Dimensions(mm)(∅xh)	89x49	105x65	123x76	151x88
Shape	Round	Round	Round	Round
Tiltable	Yes	Yes	Yes	Yes

Wattage	50W
Product Code	MRV-RZL-50
Nominal Input Voltage	240V AC, 50Hz
Luminous Flux	5000*
Color Temperature	6500K/4000K/3000K
CRI	≥80
P.F.	>0.95
THD	<10%
Surge Protection	Up to 4KV
IP Rating	IP20
Beam Angle	24°/36°/60°
Mounting	Recess
Fixture Color	White
Cutout(mm)(∅)	125
Dimensions(mm)(∅xh)	151x88
Shape	Round
Tiltable	Yes

Line Diagram

