




Aristo

Modular Highbay



Application Areas



OFFICES



BANKS



HEALTHCARE



RETAIL



EDUCATIONAL
INSTITUTE



COMMON
AREA



Aristo MODULAR HIGHBAY

IP65 WEATHERPROOF LED MODULAR HIGHBAY LIGHT

Civic-C Modular Highbay is a modern modular design made of pressuredie cast aluminium having broad heat sink fins on the backside for better heat dissipation. Modular option has got so many benefits including the easy & low maintenance due to the multiple module options.

Luminaire Details


| | |
|--------------|------------------------|
| Product Name | : Aristo |
| Product Type | : Weatherproof Highbay |
| LED Type | : SMD |
| Fixture Type | : Suspended |
| Dimmable | : Non Dimmable |

Luminaire Source Details

| | |
|----------------|-------------------------|
| Light Emission | : Indoor Space Lighting |
| Source Brand | : Bridgelux / Seoul |
| CRI | : ≥80 |
| McAdam Binning | : Step 5 |

Luminaire Housing

| | |
|-------------------------|----------------------|
| Body | : Die-Cast Aluminium |
| Reflector Type | : Polycarbonate Lens |
| Operating Temperature | : -10° to 50° C |
| Humidity | : RH 10-90 % |
| IP Rating | : IP65 |
| Emergency Compatibility | : Not Compatible |



Correlated Color Temperature

| | | | | |
|--------------------|----|----|----|----|
| Ingress Protection | LM | LM | IK | TM |
| IP65 | 79 | 80 | 07 | 21 |

Technical Specifications

| Wattage | 100W | 120W | 150W | 200W |
|-------------------------|---------------|-------------------|-------------------|----------------|
| Product Code | AR-HBL-M-50-L | AR-HBL-M-120-L | AR-HBL-M-150-L | AR-HBL-M-200-L |
| Nominal Input Voltage | 240V AC, 50Hz | 240V AC, 50Hz | 240V AC, 50Hz | 240V AC, 50Hz |
| Luminous Flux | 5000* | 10000* | 15000* | 20000* |
| Color Temperature | 6500K/ 3000K | 6500K/ 3000K | 6500K/ 3000K | 6500K/ 3000K |
| CRI | ≥80 | ≥80 | ≥80 | ≥80 |
| P.F. | >0.95 | >0.95 | >0.95 | >0.95 |
| THD | <10% | <10% | <10% | <10% |
| Surge Protection | 4KV | 4KV+10KV | 4KV+10KV | 4KV+10KV |
| IP Rating | IP65 | IP65 | IP65 | IP65 |
| Beam Angle | 90° | 90° | 90° | 90° |
| Secondary Optics (Lens) | Yes | Yes | Yes | Yes |
| Mounting | Surface | Surface/Suspended | Surface/Suspended | Suspended |
| Fixture Color | Black | Black | Black | Black |
| No. of Modules | 1 | 2 | 3 | 4 |
| Dimensions(mm)(LXWXH) | 270x156x100 | 270x234x100 | 270x234x100 | 270x312x100 |

| Wattage | 250W | 300W | 350W | 400W |
|-------------------------|----------------|-------------------|-------------------|----------------|
| Product Code | AR-HBL-M-250-L | AR-HBL-M-300-L | AR-HBL-M-350-L | AR-HBL-M-400-L |
| Nominal Input Voltage | 240V AC, 50Hz | 240V AC, 50Hz | 240V AC, 50Hz | 240V AC, 50Hz |
| Luminous Flux | 25000* | 30000* | 35000* | 40000* |
| Color Temperature | 6500K/ 3000K | 6500K/ 3000K | 6500K/ 3000K | 6500K/ 3000K |
| CRI | ≥80 | ≥80 | ≥80 | ≥80 |
| P.F. | >0.95 | >0.95 | >0.95 | >0.95 |
| THD | <10% | <10% | <10% | <10% |
| Surge Protection | 4KV | 4KV+10KV | 4KV+10KV | 4KV+10KV |
| IP Rating | IP65 | IP65 | IP65 | IP65 |
| Beam Angle | 90° | 90° | 90° | 90° |
| Secondary Optics (Lens) | Yes | Yes | Yes | Yes |
| Mounting | Surface | Surface/Suspended | Surface/Suspended | Suspended |
| Fixture Color | Black | Black | Black | Black |
| No. of Modules | 5 | 6 | 6 | 8 |
| Dimensions(mm)(LXWXH) | 270x390x100 | 540x234x100 | 540x234x100 | 540x312x100 |

Line Diagram

