




# Brillux

## Flameproof Cleanroom



### Application Areas



OFFICES



BANKS



HEALTHCARE



RETAIL



EDUCATIONAL  
INSTITUTE



COMMON  
AREA



# Brillux

## FLAMEPROOF CLEANROOM PANEL

Brillux Flameproof Cleanroom Panel are made for the chemical Industries, paint industries and pharma industries. It's made of flameproof Aluminium pressure die cast housing. Front SS frame comes with fitting which makes the aesthetic very beautiful.

### Luminaire Details


Product Name	: Brillux
Product Type	: Weatherproof Highbay
LED Type	: SMD
Fixture Type	: Suspended
Dimmable	: Non Dimmable

### Luminaire Source Details

Light Emission	: Indoor Space Lighting
Source Brand	: Bridgelux / Seoul
CRI	: ≥80
McAdam Binning	: Step 5

### Luminaire Housing

Body	: Die-Cast Aluminium
Reflector Type	: Toughened Glass
Humidity	: RH 10-90 %
IP Rating	: IP66
Emergency Compatibility	: Not Compatible



3000K 6500K



Correlated Color Temperature




# Technical Specifications

Wattage	30W	40W	45W	60W
	1x1	1x1	1x2	1x2
Product Code	BLX-FLP-30	BLX-FLP-40	BLX-FLP-45	BLX-FLP-60
Nominal Input Voltage	240V AC, 50Hz	240V AC, 50Hz	240V AC, 50Hz	240V AC, 50Hz
Luminous Flux	3000*	4000*	4500*	6000*
Color Temperature	6500K	6500K	6500K	6500K
CRI	≥80	≥80	≥80	≥80
P.F.	>0.95	>0.95	>0.95	>0.95
THD	<10%	<10%	<10%	<10%
Surge Protection	4KV+10KV (SPD)	4KV+10KV (SPD)	4KV+10KV (SPD)	4KV+10KV (SPD)
IP Rating	IP66	IP66	IP66	IP66
Beam Angle	120°	120°	120°	120°
Mounting	Ceiling Mounted	Ceiling Mounted	Ceiling Mounted	Ceiling Mounted
Fixture Color	Grey	Grey	Grey	Grey
Applicable Area	IIC T6	IIC T6	IIC T6	IIC T6
Dimensions(mm)(LXWXH)	325 x 325 x 233	325 x 325 x 233	680 x 405 x 130	680 x 405 x 130

## Line Diagram



1X1



1X2

## Photometric Details